

E1300 DEFIANT



"This boot is the result of a two year development programme with leading Oil and Gas companies. Lightweight and flexible the boot affords high levels of wearer comfort and support whilst protecting the feet to the latest standards. The sole is a special rubber compound developed for outstanding anti slip properties in hostile environments. A zip side with storm flap is incorporated for easy access."

CE SPECIFICATION

EN ISO 20345:2004 SRC S3

UPPER

Supple, water repellent and breathable S3 leather. Stitched with Kevlar for added strength the main seams are downward facing to shed water. A full bellows tongue helps to prevent ingress of dirt and water and an ergonomic padded collar provides added comfort when flexing the leg

LINING

Exclusive Soft Tex Lining - moisture wicking and highly breathable.

FOOTBED

Full length replaceable, energy return footbed incorporating rebound foam with air circulation vents.

TOECAP

Wide fitting composite non sparking and thermal insulating. Tested to 200 joule impact rating

PROTECTIVE MIDSOLE

Composite midsole.

SOLE

Triple density Phylon/Rubber providing high slip resistance. Anti-static and abrasion resistance to the latest EN standards. Heat resistant to 300°C. Acid, alkali, oil and hydrocarbon resistant. Shock absorbing defined heel for safety when working on steps/ladders.

SIZE RANGE

36(3)-(13)